

Santa Clara University
Edward M. Dowd Art and Art History Building Gallery
Exhibition Installation Policies

- Walls are backed with plywood from 3' to 11' off the ground.
- There is no need for drywall anchors or toggle bolts.
- Holes in the wall larger than 3/16" in diameter are not acceptable.
- Nails, picture hooks, and drywall screws are acceptable hanging devices.
- Adhesive attachment is not permitted on any gallery surface. This includes using glue, tape, or double sided tape.
- Labels may be affixed with small nails, DAP Bluestik brand Reusable Adhesive Putty, or can be printed on removable sticker label material.
- Gaffers tape (not duct tape) and blue painters tape are acceptable for use in the gallery.
- The walls may not be painted or directly marked on. Please use blue painters tape for layout work.
- All patching and painting must follow approved Gallery Wall Repair Procedure. Please do not paint things while attached to the wall. Do not use paint brushes for touch up work.
- The floor may not be anchored to. Please take care to protect the floor from scratches and damage, do not drag or push pedestals across floor.
- The Unistrut ceiling grid can support properly attached loads up to 150 lbs. Please do not attach things to the track light rails.
- Works of art consisting in whole or part of perishable materials, living organisms, liquids, materials covered by the Endangered Species Act, natural feathers of any kind, or deteriorating/insect infested or untreated wood will not be admitted into the exhibition.